



Everything is possible with Ventech as your Partner.



OUR FAN

A slim-line curb mounted extract fan with the lowest profile for this capacity in its class. Designed to be mounted on a flashed curb constructed by others. The covers are available in stainless steel or powder coated aluminium.

Other colour options are available, depending on availability.

https://duluxpowders.co.nz/products/ duralloy-solid/

SPEEDS

Available as a single or 3 speed fan:

VCM190–1 Single Speed VCM190–3 3 Speed

> Ideal for quiet bathroom & laundry extraction



SPECIFICATIONS


- Backward curve centrifugal rotor with integral 240V 70W 1 or 3 speed motor.
- Performance 130 Lts/sec fid- rated @ 50,000 hrs—IP55.
- Sound data: Speed 1 41 dba @ 3m
 - Speed 2 50 dba @ 3m


Speed 3 – 55 dba @ 3m



VCM190-1 B2M190-70 Single speed wiring

VCM190–3 B2M190-70-3 Three speed wiring





Ensure that fan is switched off from supply mains before removing guard. Precautions must be taken to avoid back-flow of gases into room from open flue of gas or other fuel-burning appliances. If the supply cord is damaged, it must be replaced by the manufacturer, its service agent, or similarly qualified persons. Means for disconnection must be incorporated in fixed wiring in accordance with wiring rules Appliance not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of appliance by person responsible for their safety. Children should be supervised to ensure they do not play with appliance.

GET IN TOUCH

Ventilation Technology Limited

(027) 279 6399 enquiries@ventech.co.nz www.ventech.co.nz



Christchurch, New Zealand